Printing date 13.06.2022 Revision: 20.07.2018

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Wellaflex Heat Protection Styling Spray
- · Article number: 96755416, 315000011821
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Hair care product
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

WELLA UK LTD

7t St. George's House 5 St.Wimbledon, London, SW19 4DR United Kingdom

- · Further information obtainable from: Wella SDS Info Team
- · Emergency telephone number:

CHEMTREC Emergency number: +1-703-527-3887

CHEMTREC US/NA Emergency number(toll free): 800-424-9300

CHEMTREC: +44 20 3807 3798

2 Hazards identification

flame

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

(Contd. on page 2)

Printing date 13.06.2022 Revision: 20.07.2018

Trade name: Wellaflex Heat Protection Styling Spray

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
CAS: 64-17-5	ethyl alcohol	>25-≤50%
EINECS: 200-578-6	🚸 Flam. Liq. 2, H225; 🕔 Eye Irrit. 2, H319	
CAS: 93685-81-5	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	>10-<25%
	🅸 Flam. Liq. 3, H226; 🗞 Asp. Tox. 1, H304; Aquatic Chronic 4, H413	
CAS: 107-46-0	hexamethyldisiloxane	>2.5-≤10%
EINECS: 203-492-7	🚸 Flam. Liq. 2, H225; 🔖 Aquatic Chronic 1, H410	
CAS: 56-81-5	glycerol	>2.5-≤10%
EINECS: 200-289-5	substance with a Community workplace exposure limit	
CAS: 95144-24-4	1H-imidazolium, 1-ethenyl-3-methyl-, chloride, polymer with 1-ethenyl-2-	≥0.25-<2.5%
	pyrrolidinone	
	🕸 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 13.06.2022 Revision: 20.07.2018

Trade name: Wellaflex Heat Protection Styling Spray

(Contd. of page 2)

- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

64-17-5 ethyl alcohol

WEL Long-term value: 1920 mg/m³, 1000 ppm

56-81-5 glycerol

WEL Long-term value: 10 mg/m³

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Printing date 13.06.2022 Revision: 20.07.2018

Trade name: Wellaflex Heat Protection Styling Spray

(Contd. of page 3)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: Various colours · Odour: Characteristic · Odour threshold: Not determined.

· pH-value at 20 °C: 4.5-6.5

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: Undetermined.

16 °C · Flash point:

· Flammability (solid, gas): Not applicable.

Not determined. · Decomposition temperature:

Product is not selfigniting. · Auto-ignition temperature:

Product is not explosive. However, formation of explosive air/vapour · Explosive properties: mixtures are possible.

(Contd. on page 5)

Printing date 13.06.2022 Revision: 20.07.2018

Trade name: Wellaflex Heat Protection Styling Spray

	(Contd. of page
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density:	Not determined.
Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	65.2 %
Water:	31.3 %
VOC (EC)	885.2 g/l
	60.81 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rele	vant for classification:
64-17-5 eti	hyl alcohol	
Oral	LD50	10,470 mg/kg (rat) (bw (OECD 401))
Inhalative	LC50/4 h	116.9 mg/l (rat) (air (//OECD 403))
93685-81	5 Hydroca	rbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated
Oral	LD50	>5,000 mg/kg (rat) (bw (//OECD 401))
Dermal	LD50	>2,000 mg/kg (rabbit) (bw (//OECD 402))
Inhalative	LC50/4 h	>15 mg/l (rat) (air (//OECD 403))
		(Contd. on page

Printing date 13.06.2022 Revision: 20.07.2018

Trade name: Wellaflex Heat Protection Styling Spray

		(Contd. of page 5)
107-46-0 h	examethy.	ldisiloxane
Oral	LD50	>12,160 mg/kg (rat) (bw)
Dermal	LD50	>2,000 mg/kg (rabbit) (bw (//OECD 402))
Inhalative	LC50/4 h	106 mg/l (rat) (air (OECD 403))
56-81-5 gl	ycerol	
Oral	LD50	23,000 mg/kg (rat)
Dermal	LD50	56,745 mg/kg (rabbit)
Inhalative	LC50/4 h	4,655 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.}$
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 13.06.2022 Revision: 20.07.2018

Trade name: Wellaflex Heat Protection Styling Spray

(Contd. of page 6)

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

JN-Number	
ADR/RID/ADN, IMDG, IATA	UN1266
UN proper shipping name	
ADR/RID/ADN	1266 PERFUMERY PRODUCTS
MDG, IATA	PERFUMERY PRODUCTS
Transport hazard class(es)	
ADR/RID/ADN, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group	
ADR/RID/ADN, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F- E , S - D
Stowage Category	В
Transport in bulk according to Annex II of Marp	
and the IBC Code	Not applicable.
Transport/Additional information:	
ADR/RID/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
Tuguam out og tog om:	Maximum net quantity per outer packaging: 500 ml 2
Transport category Tunnel restriction code	D/E
	υιτ
MDG	51
Limited quantities (LQ) Executed quantities (EQ)	5L Code: E2
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml

Printing date 13.06.2022 Revision: 20.07.2018

Trade name: Wellaflex Heat Protection Styling Spray

(Contd. of page 7)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

- · Department issuing SDS: Abteilung Umweltschutz
- · Contact: Hr. Dr. Speckbacher
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4